

20181-00

MICROPHONE ACCESS STATION



Features:

- 4 Alarm selection switches
- 4 Zone selection switches.
- 1 Emergency call switch.
- 1 Press-to-talk (PTT) switch for paging.
- Status LED, monitors the communication status of the PAGA Controller

Industrial grade access panel, built for harsh and corrosive environment. The module includes a microphone that features a low-impedance moving coil type transducer with an integral hum bucking coil; it produces a frequency response with an essentially constant output voltage over the voice spectrum when used close to the sound source.

It offers excellent voice fidelity while reducing background noise.

A stylish flush mount switches seamlessly integrated into the panel. Its vivid colors and two-tone brightness enhances the visibility of the control switches during operation

Two RS-485 transmission lines are used for control and monitoring that will guarantee a fail-safe operation.

SPECIFICATION

| Model | 20181-00 |
|--------------------------------------|---|
| Microphone Type | Noise-cancelling Dynamic |
| Frequency Response | 100 - 6,000 Hz |
| Output Level | 0.6mV |
| Signal to Noise Ratio (SNR) | > 70dB |
| Total Harmonic Distortion (THD) | < 1% |
| Power Supply | 24VDC |
| Mechanical Selection Switches | |
| Controls | Industrial grade, Illuminated mechanical switches |
| Mechanical Life | 1,000,000 (minimum operation) |
| Vibration resistance | 5 to 55 Hz |
| Degree of protection | IP65 (IEC 60529) |



20181-00

MICROPHONE ACCESS STATION

| | |
|--------------|-----------------------|
| Model | CA-MS04 |
| Weight | ? |
| Dimensions | 250mm x 160mm x 190mm |

DIMENSIONS (in mm)

